

**FEATURES:**

- RoHS Compliant
- 8 Pin Dip Package
- Low Ripple and Noise
- High Efficiency Up To 78%
- Operating Temperature -40°C to +85°C
- Input / Output Isolation 1000 & 3000 VDC
- Pin Compatible with Multiple Manufacturers
- Continuous Short Circuit Protection



Models

Single output

| Model | Input Voltage (V) | Output Voltage (V) | Output Current Max (mA) | Isolation (VDC) | Input Current Full Load No Load (mA) | | Max Capacitive Load (µF) | Efficiency (%) |
|-----------------|-------------------|--------------------|-------------------------|-----------------|--|----|--------------------------|----------------|
| AM1PS-0505SZ | 4.5-5.5 | 5 | 200 | 1000 | 267 | 53 | 100 | 75 |
| AM1PS-0512SZ | 4.5-5.5 | 12 | 83.3 | 1000 | 270 | 48 | 100 | 74 |
| AM1PS-0515SZ | 4.5-5.5 | 15 | 66.6 | 1000 | 173 | 50 | 100 | 79 |
| AM1PS-1205SZ | 10.8-13.2 | 5 | 200 | 1000 | 110 | 20 | 100 | 76 |
| AM1PS-1212SZ | 10.8-13.2 | 12 | 83.3 | 1000 | 111 | 20 | 100 | 78 |
| AM1PS-1215SZ | 10.8-13.2 | 15 | 66.6 | 1000 | 111 | 30 | 100 | 79 |
| AM1PS-2405SZ | 21.6-26.4 | 5 | 200 | 1000 | 58 | 20 | 100 | 72 |
| AM1PS-2412SZ | 21.6-26.4 | 12 | 83.3 | 1000 | 56 | 15 | 100 | 74 |
| AM1PS-2415SZ | 21.6-26.4 | 15 | 66.6 | 1000 | 56 | 15 | 100 | 74 |
| AM1PS-0505SH30Z | 4.5-5.5 | 5 | 200 | 3000 | 267 | 53 | 100 | 75 |
| AM1PS-0512SH30Z | 4.5-5.5 | 12 | 83.3 | 3000 | 270 | 48 | 100 | 74 |
| AM1PS-0515SH30Z | 4.5-5.5 | 15 | 66.6 | 3000 | 173 | 50 | 100 | 79 |
| AM1PS-1205SH30Z | 10.8-13.2 | 5 | 200 | 3000 | 110 | 20 | 100 | 76 |
| AM1PS-1212SH30Z | 10.8-13.2 | 12 | 83.3 | 3000 | 111 | 20 | 100 | 78 |
| AM1PS-1215SH30Z | 10.8-13.2 | 15 | 66.6 | 3000 | 111 | 30 | 100 | 79 |
| AM1PS-2405SH30Z | 21.6-26.4 | 5 | 200 | 3000 | 58 | 20 | 100 | 72 |
| AM1PS-2412SH30Z | 21.6-26.4 | 12 | 83.3 | 3000 | 56 | 15 | 100 | 74 |
| AM1PS-2415SH30Z | 21.6-26.4 | 15 | 66.6 | 3000 | 56 | 15 | 100 | 74 |

NOTE: All specifications in this datasheet are measured at an ambient temperature of 25°C, humidity < 75%, nominal input voltage and at rated output load unless otherwise specified

Input Specifications

| Parameters | Nominal | Typical | Maximum | Units |
|--------------------------------|-----------------------------|-----------|---------|--------|
| Voltage range | 5 | 4.5-5.5 | | VDC |
| | 12 | 10.8-13.2 | | |
| | 24 | 21.6-26.4 | | |
| Filter | Capacitor | | | |
| Absolute Maximum Rating | 5 Vin | 0-7 | | VDC |
| | 12 Vin | 0-15 | | |
| | 24 Vin | 0-28 | | |
| Peak Input Voltage time | | | 100 | ms |
| Input Reflected Ripple current | With 12µH source inductance | | 20 | mA p-p |

Isolation Specifications

| Parameters | Conditions | Typical | Rated | Units |
|--------------------|------------|---------|---------------|-------|
| Tested I/O voltage | 60sec | | 1000 and 3000 | VDC |
| Resistance | | > 1000 | | MOhm |
| Capacitance | | 10 | | pF |

Output Specifications

| Parameters | Conditions | Typical | Maximum | Units |
|--------------------------|------------|---------------|---------|-------|
| Voltage accuracy | | ±3 | | % |
| Short Circuit protection | | Continuous | | |
| Short circuit restart | | Auto-Recovery | | |

| | | | | |
|-------------------------|----------------------|-------|--|--------|
| Line voltage regulation | For 1% change of Vin | ±1.2 | | % |
| Load voltage regulation | Load 20 – 100% | ±10 | | % |
| Temperature coefficient | | ±0.02 | | %/°C |
| Ripple & Noise | At 20MHz Bandwidth | 100 | | mV p-p |

General Specifications

| Parameters | Conditions | Typical | Maximum | Units |
|------------------------|---|-------------|---------|-------|
| Switching frequency | 100% load, Variable | 80 | | KHz |
| Operating temperature | Full Load without Derating | -40 to +85 | | °C |
| Storage temperature | | -40 to +125 | | °C |
| Max Case temperature | | | 100 | °C |
| Cooling | Free air convection | | | |
| Humidity | | | 95 | % |
| Case material | Non-conductive black plastic | | | |
| Weight | | 1.8 | | g |
| Dimensions (L x W x H) | 0.50 x 0.40 x 0.27 inches 12.70 x 10.16 x 6.85 mm | | | |
| MTBF | >1 121 000 hrs (MIL-HDBK -217F, Ground Benign, t=+25°C) | | | |


Safety Specifications

| Parameters | |
|------------|---|
| Standards | Designed to meet IEC 60950-1 |
| | EN55032 Class A, with external components |
| | IEC61000-4-2, Perf. Criteria A |
| | IEC61000-4-3, Perf. Criteria A |
| | IEC61000-4-4, Perf. Criteria A |
| | IEC61000-4-5, Perf. Criteria A |
| | IEC61000-4-6, Perf. Criteria A |
| | IEC61000-4-8, Perf. Criteria A |


Pin Out Specifications



| Pin | 1000 and 3000 VDC | |
|-----|-------------------|------------|
| | Single | Dual |
| 1 | - V Input | - V Input |
| 4 | + V Input | + V Input |
| 5 | + V Output | + V Output |
| 6 | No pin | No pin |
| 7 | - V Output | Common |
| 8 | No pin | - V Output |

Dimensions



Typical Efficiency Example Charts





NOTE: **1.** Datasheets are updated as needed and as such, specifications are subject to change without notice. Once printed or downloaded, datasheets are no longer controlled by Aimtec; refer to www.aimtec.com for the most current product specifications. **2.** Product labels shown, including safety agency certifications on labels, may vary based on the date manufactured. **3.** Mechanical drawings and specifications are for reference only. **4.** All specifications are measured at an ambient temperature of 25°C, humidity < 75%, nominal input voltage and at rated output load unless otherwise specified. **5.** Aimtec may not have conducted destructive testing or chemical analysis on all internal components and chemicals at the time of publishing this document. CAS numbers and other limited information are considered proprietary and may not be available for release. **6.** This product is not designed for use in critical life support systems, equipment used in hazardous environments, nuclear control systems or other such applications which necessitate specific safety and regulatory standards other than the ones listed in this datasheet. **7.** Warranty is in accordance with Aimtec's standard Terms of Sale available at www.aimtec.com.